

PATENTTI- JA REKISTERIHALLITUS
NATIONAL BOARD OF PATENTS AND REGISTRATION

Helsinki 16.02.2000

ETUOIKEUSTODISTUS
PRIORITY DOCUMENT

jc525 U.S. PTO
09/513704
02/25/00



Hakija
Applicant

1. Sonera Oy
Helsinki, FI
2. Linkola, Janne
Espoo, FI
3. Hokkanen, Tuomo
Helsinki, FI

Kansainvälinen patenttihakemus nro
International patent application no PCT/FI98/00653

Kansainvälinen tekemispäivä
International filing date 25.08.1998

Etuoikeushak. nro
Priority from appl. FI 973528

Tekemispäivä
Filing date 27.08.1997

Keksinnön nimitys
Title of invention

"Procedure for accessing a service in a data communication system,
and a data communication system"

Täten todistetaan, että oheiset asiakirjat ovat tarkkoja jäljennöksiä kansainvälisiä patenttihakemuksia vastaanottavana viranomaisena toimivalle Patentti- ja rekisterihallitukselle alkuaan annetuista selityksestä, patenttivaatimuksista ja tiivistelmästä sekä niihin tehdyistä korjauksista.

This is to certify that the annexed documents are true copies of the description, claims, and abstract, originally filed with the Finnish Patent Office acting as receiving Office for the international patent applications, and of any corrections thereto.


Pirjo Kaila
Tutkimussihteeri

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

Maksu 300,- mk
Fee 300,- FIM

Osoite: Arkadiankatu 6 A
Address: P.O.Box 1160
FIN-00101 Helsinki, FINLAND

Puhelin: 09 6939 500
Telephone: + 358 9 6939 500

Telefax: 09 6939 5204
Telefax: + 358 9 6939 5204

HOME COPY PCT

REQUEST

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For receiving Office use only	
International Application No.	PCT/FI 9 8 / 0 0 6 5 3
International Filing Date	2 5 AUG 1998 (2 5. 08. 98)
The Finnish Patent Office PCT International Application	
Name of receiving Office and "PCT International Application"	
Applicant's or agent's file reference (if desired) (12 characters maximum)	10686S

Box No. I	TITLE OF INVENTION		PROCEDURE FOR ACCESSING A SERVICE IN A DATA COMMUNICATION SYSTEM, AND A DATA COMMUNICATION SYSTEM
Box No. II	APPLICANT		
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)		<input type="checkbox"/> This person is also inventor.	
SONERA OY Sturenkatu 16 FIN-00510 HELSINKI Finland		Telephone No.	
		Facsimile No.	
		Teleprinter No.	
State (that is, country) of nationality: FI		State (that is, country) of residence: FI	
This person is applicant for the purposes of: <input type="checkbox"/> all designated States <input checked="" type="checkbox"/> all designated States except the United States of America <input type="checkbox"/> the United States of America only <input type="checkbox"/> the States indicated in the Supplemental Box			
Box No. III	FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)		
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)		This person is:	
LINKOLA, Janne Kuusikallionkuja 4 F 43 FIN-02210 ESPOO Finland		<input type="checkbox"/> applicant only <input checked="" type="checkbox"/> applicant and inventor <input type="checkbox"/> inventor only (If this check-box is marked, do not fill in below.)	
State (that is, country) of nationality: FI		State (that is, country) of residence: FI	
This person is applicant for the purposes of: <input type="checkbox"/> all designated States <input type="checkbox"/> all designated States except the United States of America <input checked="" type="checkbox"/> the United States of America only <input type="checkbox"/> the States indicated in the Supplemental Box			
<input checked="" type="checkbox"/> Further applicants and/or (further) inventors are indicated on a continuation sheet.			
Box No. IV	AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR CORRESPONDENCE		
The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:		<input checked="" type="checkbox"/> agent <input type="checkbox"/> common representative	
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country.)		Telephone No.	
PAPULA REIN LAHTELA OY P.O. Box 981 (Fredrikinkatu 61 A) FIN-00101 Helsinki Finland		+358 9 3480 060	
		Facsimile No.	
		+358 9 3480 0630	
		Teleprinter No.	
<input type="checkbox"/> Address for correspondence: Mark this check-box where no agent or common representative is/has been appointed and the space above is used instead to indicate a special address to which correspondence should be sent.			

Continuation of Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)

If none of the following sub-boxes is used, this sheet should not be included in the request.

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)

HOKKANEN, Tuomo
Strömsinlahdenkuja 2 A 13
FIN-00820 HELSINKI
Finland

This person is:

- ☐ applicant only
☒ applicant and inventor
☐ inventor only (If this check-box is marked, do not fill in below.)

State (that is, country) of nationality:
FI

State (that is, country) of residence:
FI

This person is applicant for the purposes of:

- ☐ all designated States ☐ all designated States except the United States of America ☒ the United States of America only ☐ the States indicated in the Supplemental Box

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)

This person is:

- ☐ applicant only
☐ applicant and inventor
☐ inventor only (If this check-box is marked, do not fill in below.)

State (that is, country) of nationality:

State (that is, country) of residence:

This person is applicant for the purposes of:

- ☐ all designated States ☐ all designated States except the United States of America ☐ the United States of America only ☐ the States indicated in the Supplemental Box

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)

This person is:

- ☐ applicant only
☐ applicant and inventor
☐ inventor only (If this check-box is marked, do not fill in below.)

State (that is, country) of nationality:

State (that is, country) of residence:

This person is applicant for the purposes of:

- ☐ all designated States ☐ all designated States except the United States of America ☐ the United States of America only ☐ the States indicated in the Supplemental Box

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)

This person is:

- ☐ applicant only
☐ applicant and inventor
☐ inventor only (If this check-box is marked, do not fill in below.)

State (that is, country) of nationality:

State (that is, country) of residence:

This person is applicant for the purposes of:

- ☐ all designated States ☐ all designated States except the United States of America ☐ the United States of America only ☐ the States indicated in the Supplemental Box

☐ Further applicants and/or (further) inventors are indicated on another continuation sheet.

Box No.V DESIGNATION OF STATES

The following designations are hereby made under Rule 4.9(a) (mark the applicable check-boxes; at least one must be marked):

Regional Patent

- ☒ AP ARIPO Patent: GH Ghana, GM Gambia, KE Kenya, LS Lesotho, MW Malawi, SD Sudan, SZ Swaziland, UG Uganda, ZW Zimbabwe, and any other State which is a Contracting State of the Harare Protocol and of the PCT
- ☒ EA Eurasian Patent: AM Armenia, AZ Azerbaijan, BY Belarus, KG Kyrgyzstan, KZ Kazakhstan, MD Republic of Moldova, RU Russian Federation, TJ Tajikistan, TM Turkmenistan, and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT
- ☒ EP European Patent: AT Austria, BE Belgium, CH and LI Switzerland and Liechtenstein, CY Cyprus, DE Germany, DK Denmark, ES Spain, FI Finland, FR France, GB United Kingdom, GR Greece, IE Ireland, IT Italy, LU Luxembourg, MC Monaco, NL Netherlands, PT Portugal, SE Sweden, and any other State which is a Contracting State of the European Patent Convention and of the PCT
- ☒ OA OAPI Patent: BF Burkina Faso, BJ Benin, CF Central African Republic, CG Congo, CI Côte d'Ivoire, CM Cameroon, GA Gabon, GN Guinea, ML Mali, MR Mauritania, NE Niger, SN Senegal, TD Chad, TG Togo, and any other State which is a member State of OAPI and a Contracting State of the PCT (if other kind of protection or treatment desired, specify on dotted line)

National Patent (if other kind of protection or treatment desired, specify on dotted line):

- | | |
|--|--|
| <input checked="" type="checkbox"/> AL Albania | <input checked="" type="checkbox"/> LS Lesotho |
| <input checked="" type="checkbox"/> AM Armenia | <input checked="" type="checkbox"/> LT Lithuania |
| <input checked="" type="checkbox"/> AT Austria | <input checked="" type="checkbox"/> LU Luxembourg |
| <input checked="" type="checkbox"/> AU Australia | <input checked="" type="checkbox"/> LV Latvia |
| <input checked="" type="checkbox"/> AZ Azerbaijan | <input checked="" type="checkbox"/> MD Republic of Moldova |
| <input checked="" type="checkbox"/> BA Bosnia and Herzegovina | <input checked="" type="checkbox"/> MG Madagascar |
| <input checked="" type="checkbox"/> BB Barbados | <input checked="" type="checkbox"/> MK The former Yugoslav Republic of Macedonia |
| <input checked="" type="checkbox"/> BG Bulgaria | |
| <input checked="" type="checkbox"/> BR Brazil | <input checked="" type="checkbox"/> MN Mongolia |
| <input checked="" type="checkbox"/> BY Belarus | <input checked="" type="checkbox"/> MW Malawi |
| <input checked="" type="checkbox"/> CA Canada | <input checked="" type="checkbox"/> MX Mexico |
| <input checked="" type="checkbox"/> CH and LI Switzerland and Liechtenstein | <input checked="" type="checkbox"/> NO Norway |
| <input checked="" type="checkbox"/> CN China | <input checked="" type="checkbox"/> NZ New Zealand |
| <input checked="" type="checkbox"/> CU Cuba | <input checked="" type="checkbox"/> PL Poland |
| <input checked="" type="checkbox"/> CZ Czech Republic | <input checked="" type="checkbox"/> PT Portugal |
| <input checked="" type="checkbox"/> DE Germany | <input checked="" type="checkbox"/> RO Romania |
| <input checked="" type="checkbox"/> DK Denmark | <input checked="" type="checkbox"/> RU Russian Federation |
| <input checked="" type="checkbox"/> EE Estonia | <input checked="" type="checkbox"/> SD Sudan |
| <input checked="" type="checkbox"/> ES Spain | <input checked="" type="checkbox"/> SE Sweden |
| <input checked="" type="checkbox"/> FI Finland | <input checked="" type="checkbox"/> SG Singapore |
| <input checked="" type="checkbox"/> GB United Kingdom | <input checked="" type="checkbox"/> SI Slovenia |
| <input checked="" type="checkbox"/> GE Georgia | <input checked="" type="checkbox"/> SK Slovakia |
| <input checked="" type="checkbox"/> GH Ghana | <input checked="" type="checkbox"/> SL Sierra Leone |
| <input checked="" type="checkbox"/> GM Gambia | <input checked="" type="checkbox"/> TJ Tajikistan |
| <input checked="" type="checkbox"/> GW Guinea-Bissau | <input checked="" type="checkbox"/> TM Turkmenistan |
| <input checked="" type="checkbox"/> HR Croatia | <input checked="" type="checkbox"/> TR Turkey |
| <input checked="" type="checkbox"/> HU Hungary | <input checked="" type="checkbox"/> TT Trinidad and Tobago |
| <input checked="" type="checkbox"/> ID Indonesia | <input checked="" type="checkbox"/> UA Ukraine |
| <input checked="" type="checkbox"/> IL Israel | <input checked="" type="checkbox"/> UG Uganda |
| <input checked="" type="checkbox"/> IS Iceland | <input checked="" type="checkbox"/> US United States of America |
| <input checked="" type="checkbox"/> JP Japan | |
| <input checked="" type="checkbox"/> KE Kenya | <input checked="" type="checkbox"/> UZ Uzbekistan |
| <input checked="" type="checkbox"/> KG Kyrgyzstan | <input checked="" type="checkbox"/> VN Viet Nam |
| <input checked="" type="checkbox"/> KP Democratic People's Republic of Korea | <input checked="" type="checkbox"/> YU Yugoslavia |
| | <input checked="" type="checkbox"/> ZW Zimbabwe |
| <input checked="" type="checkbox"/> KR Republic of Korea | |
| <input checked="" type="checkbox"/> KZ Kazakhstan | |
| <input checked="" type="checkbox"/> LC Saint Lucia | |
| <input checked="" type="checkbox"/> LK Sri Lanka | |
| <input checked="" type="checkbox"/> LR Liberia | |

Check-boxes reserved for designating States (for the purposes of a national patent) which have become party to the PCT after issuance of this sheet:

- ☐
- ☐

Precautionary Designation Statement: In addition to the designations made above, the applicant also makes under Rule 4.9(b) all other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded from the scope of this statement. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation of a designation consists of the filing of a notice specifying that designation and the payment of the designation and confirmation fees. Confirmation must reach the receiving Office within the 15-month time limit.)

Box No. VI PRIORITY CLAIM		<input type="checkbox"/> Further priority claims are indicated in the Supplemental Box.		
Filing date of earlier application (day/month/year)	Number of earlier application	Where earlier application is:		
		national application: country	regional application: * regional Office	international application: receiving Office
item (1) 27 August 1997 (27.08.97)	973528	FI		
item (2)				
item (3)				

☐ The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) (only if the earlier application was filed with the Office which for the purposes of the present international application is the receiving Office) identified above as item(s):

* Where the earlier application is an ARIPO application, it is mandatory to indicate in the Supplemental Box at least one country party to the Paris Convention for the Protection of Industrial Property for which that earlier application was filed (Rule 4.10(b)(ii)). See Supplemental Box.

Box No. VII INTERNATIONAL SEARCHING AUTHORITY

Choice of International Searching Authority (ISA) (if two or more International Searching Authorities are competent to carry out the international search, indicate the Authority chosen; the two-letter code may be used):

ISA / SE

Request to use results of earlier search; reference to that search (if an earlier search has been carried out by or requested from the International Searching Authority):

Date (day/month/year)

Number

Country (or regional Office)

Box No. VIII CHECK LIST; LANGUAGE OF FILING

This international application contains the following number of sheets:

request : 4

description (excluding sequence listing part) : 9

claims : 4

abstract : 1

drawings :

sequence listing part of description :

Total number of sheets : 18

This international application is accompanied by the item(s) marked below:

1. ☒ fee calculation sheet
2. ☐ separate signed power of attorney
3. ☒ copy of general power of attorney; reference number, if any:
4. ☐ statement explaining lack of signature
5. ☐ priority document(s) identified in Box No. VI as item(s):
6. ☐ translation of international application into (language):
7. ☐ separate indications concerning deposited microorganism or other biological material
8. ☐ nucleotide and/or amino acid sequence listing in computer readable form
9. ☐ other (specify):

Figure of the drawings which should accompany the abstract:

Language of filing of the international application:

English

Box No. IX SIGNATURE OF APPLICANT OR AGENT

Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request).

PAPULA REIN LAHTELA OY



Markku Simmelvuo

For receiving Office use only		2. Drawings: <input type="checkbox"/> received: <input type="checkbox"/> not received:
1. Date of actual receipt of the purported international application:	25 AUG 1998	
3. Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application:		
4. Date of timely receipt of the required corrections under PCT Article 11(2):		
5. International Searching Authority (if two or more are competent): ISA / SE	6. <input type="checkbox"/> Transmittal of search copy delayed until search fee is paid.	

For International Bureau use only
Date of receipt of the record copy by the International Bureau:

PROCEDURE FOR ACCESSING A SERVICE IN A DATA
COMMUNICATION SYSTEM, AND A DATA COMMUNICATION SYSTEM

The present invention relates to a procedure
as defined in the preamble of claim 1. Moreover, the
5 invention relates to a system as defined in the pream-
ble of claim 6.

Reliable user identification is a prerequi-
site for the use of many services provided in the gen-
eral telecommunication network or in other data net-
10 works. Such services include e.g. bank services. The
service may involve significant economic effects and
therefore the service provider wants to ascertain the
user's identity before making the service available.

Very often, e.g. in conjunction with bank
15 services, the user is identified by means of pass-
words. Usually these passwords are expendable. The
service provider or an identifying party authorised by
the service provider has given the user beforehand a
number of passwords (e.g. four-digit numbers), one of
20 which the customer uses each time he/she needs the
services. When a list of passwords is about to be ex-
hausted, the service provider (or a party authorised
by the service provider) sends the user a new list of
passwords. Thus, the user always has a sufficient num-
25 ber of passwords for his/her needs in the near future.

A feature typical of prior-art solutions is
that the customer has to manually input an expendable
password when logging on to a server. Often the pass-
word is entered by pressing the keys of a telephone
30 set, causing the data to be transmitted to the server
using tone frequency transmission, so-called DTMF
(dual tone multifrequency) codes. In addition, there
are many other methods for transmitting a password,
such as the short-message service in the GSM network
35 (GSM, Global System for Mobile Communications; in the
present description, GSM network refers to any mobile
communication system based on the GSM specifications).

However, the essential point is that the user has to manually input the password him/herself. This is in many cases quite difficult for the user.

Another feature typical of prior-art solutions is that the service provider must send a new set of passwords by using a rather unreliable transmission mechanism. The most commonly used method is to send them by mail. The problem is that the letter containing the passwords may end up in the wrong hands.

10 The object of the present invention is to eliminate the problems described above.

A specific object of the present invention is to disclose a completely new type of procedure and system for transmitting passwords between a user's
15 telephone apparatus and a server.

A further object of the invention is to facilitate the use of services requiring passwords by reducing the number of routines necessitating user interaction in conjunction with the use of the services
20 without making any compromises in regard of safety of the services.

The procedure of the invention is characterised by what is presented in claim 1. The system of the invention is characterised by what is presented in
25 claim 6.

In the procedure of the invention for accessing a service in a data communication system, in which the service provider gives the user of a service a number of expendable passwords by means of which the
30 user can access the service via a telecommunication and/or data network, a connection is set up from a terminal device to a server and a password is sent at log-on to the service, the password is identified and access to the service is allowed and/or denied based
35 on the password supplied.

According to the invention, in the procedure, a set of passwords are stored in the terminal device,

the right password is selected from the stored set of passwords at log-on to a predetermined service, and the password is automatically added to a connection setup signal to be transmitted from the terminal device to the server.

Correspondingly, in the system of the invention, the terminal device comprises means for storing a set of passwords and selecting the right password from the stored set of passwords at log-on to a predetermined service to allow automatic addition of the password to a connection setup signal to be transmitted from the terminal device to the server.

The invention has the advantage that it discloses a completely new type of mechanism for the transmission of passwords between a user's telephone apparatus and a server. A further advantage of the invention is that it facilitates the use of services requiring passwords by reducing the number of routines necessitating user interaction in conjunction with the use of the services. This is done without any compromises regarding the safety of the services.

In an embodiment of the procedure, the used ones of the passwords in a set of passwords are registered.

In an embodiment of the procedure, the set of passwords in the terminal device is updated from the server via the telecommunication and/or data network.

In an embodiment of the procedure, an order for a new set of passwords is automatically sent to the server once the previous set of passwords has been exhausted.

In an embodiment of the procedure, several sets of passwords corresponding to different services are stored in the terminal device, and in connection setup the set of passwords corresponding to the service to be accessed in each case is selected.

In an embodiment of the system, the terminal device comprises means for registering the used ones of the passwords in a set of passwords.

5 In an embodiment of the system, the server comprises means for updating the set of passwords in the terminal device via a telecommunication and/or data network, and the terminal device comprises means for receiving a set of passwords.

10 In an embodiment of the system, the terminal device comprises means for automatic ordering of a new set of passwords from the server after the previous set of passwords has been exhausted.

15 In an embodiment of the system, the terminal device comprises means for storing several sets of passwords corresponding to different services.

In an embodiment of the system, the terminal device comprises means for selecting the set of passwords corresponding to the service to be used in each case.

20 In an embodiment of the system, the data communication system comprises a wired network and the terminal device is a telecommunication terminal, such as a telephone, in the wired network.

25 In an embodiment of the system, the data communication system comprises a mobile communication network, such as a GSM network, and the terminal device is a mobile station, such as a GSM telephone.

30 In an embodiment of the system, the terminal device is a GSM telephone, and the means for using said password management functions are disposed in a subscriber identity module, such as a SIM card.

35 In an embodiment of the system, in the connection setup between the subscriber identity module and the server, the transmission of passwords is effected by making use of the called subscriber number.

In an embodiment of the system, the software means of the subscriber identity module are designed

to identify the service on the basis of its identifier data, such as the telephone number, and to add a number of additional digits forming a password to the end of the telephone number of the service during call
5 setup.

In an embodiment of the system, the subscriber identity module is provided with a service directory containing information specifying the services, the service identifier data and the names of the
10 password files to be used in conjunction with the services.

In an embodiment of the system, the service directory is provided with a pointer for each service, which pointer has been arranged to point to the first
15 unused password in the set of passwords and, after the password has been used, to move on to point to the next unused password in sequence.

In an embodiment of the system, the means for ordering new passwords and transmitting them between
20 the server and the subscriber identity module comprise the short-message service (SMS-PP service) of the GSM network.

In the following, the invention will be described in detail by the aid of an application exam-
25 ple.

The invention is based on providing the telephone apparatus with an extra module (physical or logical) allowing a functionality which creates additional signals in the communication between the tele-
30 phone apparatus and the server in conjunction with a connection setup related to a service and/or additional fields and/or components or equivalent in the communication between the telephone apparatus and the server, the expendable password being transmitted in
35 these additional signals/fields/components. This is done automatically without the user becoming aware of it. The module registers the passwords used each time

and therefore always knows which is the correct password to be used at log-on. The user will find this type of services easier to use, but in respect of data security they are of the same level with services in
5 which the user must input the passwords him/herself. The extra module is also able to receive new passwords from the server and it can even order new passwords when necessary.

The extra module in the telephone apparatus
10 may support simultaneous services requiring expendable passwords. For this purpose, the extra module contains a directory of services supported (in short, a service directory), which is used to identify a service requiring expendable passwords and to find the correct
15 list of passwords and also to find the correct position in the list.

The best embodiment of the invention is a mobile station, such as a GSM telephone, whose subscriber identity module contains an application that
20 uses SIM Application Toolkit commands to accomplish the extra functionality described above. The password transmission mechanism used in conjunction with the setup of a service connection between the SIM card and the server consists of the use of the called subscriber number, i.e. the so-called B-identifier. The
25 application on the SIM card uses the 'Call Control by SIM' command as defined in the TS GSM 11.14 specification, and in practice the application processes each called subscriber number, in other words, it compares
30 the called subscriber number with the numbers stored in the service directory, and when it detects that the call is addressed to one of the stored numbers, it appends to the end of the telephone number a required number of additional digits in which the expendable
35 password is encoded. For example, when the user is making a call to the number 0800-XYZ-123456, the application on the SIM card will change the number to

the form 0800-XYZ-123456-KLMN. The last four digits (KLMN) of the modified number are the expendable password added by the SIM card.

The service directory may be implemented as a special file on the SIM card. The special file contains information specifying the services supported, their identifier data and the names of the password files to be used in conjunction with the services. Moreover, for each service, the service directory contains a pointer that points to the current position in the list of passwords. Table 1 presents an example of the information elements contained in the special file.

For example, service 1 is identified from the fact that the user is calling the number 0800123. The application knows that it has to append to the end of the number an expendable password, which is found in the file 2FF5. In this instance, the password to be used is the thirteenth one in this file.

20

Service identifier	Method	Identifiers associated with method	Name of password file	Pointer	Total number of passwords
1	BID	0800123	2FF5	13	100
2	BID	0800456	2FF4	11	100
3	SMS	SMSC:+02 0202800 BID:8756	2FF6	2	9

Table 1. Service directory as used in an embodiment of the invention.

The server in the public telecommunication network receives the expendable password in the signalling in the telephone network. The server takes the last four digits of the B-identifier and assumes that they constitute an expendable password. The server

compares the expendable password thus obtained with its own information as to the user's next password. This is done by methods already known at present.

If the service requires the use of a user
5 name at log-on to the service, the service directory may contain stored user names for each service. The user name can be appended to the connection setup signal in the same way as the password.

For the transmission of new passwords between
10 the server and the application of the invention on the SIM card, it is possible to use the SMS-PP service of the GSM network. If the SIM card sends an order for new passwords, this is effected using the SMS-PP/MO (Mobile Originated) service and the passwords are
15 transmitted to the SIM card using the SMS/PP-MT service.

The functionality of the application is divided between three blocks. The first block, an appending block, recognises the need to add an expend-
20 able password and sends a request to find the password to a password search block. Once the search block has found the right password, the appending block appends the expendable password it has received to the B-identifier and allows the call to proceed further from
25 the telephone apparatus.

In the best embodiment of the invention, a block for adding new passwords works completely independently of the other blocks. In practice, it monitors the SMS Data Download traffic consistent with TS
30 GSM 11.14 version 5.1.0 received by the SIM card and detects the appearance of new passwords on the card. The block for adding new passwords stores the new passwords received in the SMS Data Download message to a suitable special file on the SIM card and makes an
35 appropriate addition to the service directory so that the search block will be able to find the new passwords. This new password file may be a combination

that contains the last unused passwords of the previous file and the completely new passwords just received.

5 The invention is not restricted to the application example described above, but many variations are possible within the scope of the inventive idea defined by the claims.

CLAIMS

1. Procedure for accessing a service in a data communication system, in which the user of the service is given a set of expendable passwords that
5 the user can use to access the service via a telecommunication and/or data network, and in which procedure a terminal device is used to set up a connection to a server and a password is sent at log-on to the service, the password is identified and access to the
10 service is allowed/denied based on the password supplied; characterised in that

a set of passwords is stored in the terminal device,

the right password is selected from the
15 stored set of passwords at log-on to a predetermined service, and

the password is automatically added to a connection setup signal to be transmitted from the terminal device to the server.

20 2. Procedure as defined in claim 1, characterised in that the used ones of the passwords in a set of passwords are registered.

3. Procedure as defined in claim 1 or 2, characterised in that the set of passwords in
25 the terminal device is updated from the server via the telecommunication and/or data network.

4. Procedure as defined in any one of claims 1 - 3, characterised in that an order for a new set of passwords is automatically sent to the
30 server once the preceding set of passwords has been exhausted.

5. Procedure as defined in any one of claims 1 - 4, characterised in that several sets of passwords corresponding to different services are
35 stored in the terminal device and, during connection setup, the set of passwords corresponding to the service to be accessed in each case is selected.

6. Data communication system in which the user of a service is given a set of expendable passwords that the user can use to access the service via a telecommunication and/or data network, said system
5 comprising

- a user's terminal device provided with means for sending a password at log-on to the service,
- a server to which the terminal device sets up a connection, said server comprising means for
10 identifying the password and for allowing/denying access to the service on the basis of the password supplied, characterised in that the terminal device comprises means for storing a set of passwords and selecting the right password from the stored set
15 of passwords at log-on to a predetermined service to allow automatic addition of the password to a connection setup signal to be transmitted from the terminal device to the server.

7. System as defined in claim 6, characterised in that the terminal device comprises means for registering the used ones of the passwords in the set of passwords.

8. System as defined in claim 6 or 7, characterised in that the server comprises
25 means for updating the set of passwords in the terminal device via the telecommunication and/or data network, and that the terminal device comprises means for receiving a set of passwords.

9. System as defined in any one of claims 6 -
30 8, characterised in that the terminal device comprises means for automatic ordering of a new set of passwords from the server after the previous set of passwords has been exhausted.

10. System as defined in any one of claims 6
35 - 9, characterised in that the terminal device comprises means for storing several sets of passwords corresponding to different services.

11. System as defined in claim 10, characterised in that the terminal device comprises means for selecting the set of passwords corresponding to the service to be used in each case.

5 12. System as defined in any one of claims 6 - 11, characterised in that the data communication system comprises a wired network and the terminal device is a telecommunication terminal, such as a telephone, in the wired network.

10 13. System as defined in any one of claims 6 - 12, characterised in that the data communication system comprises a mobile communication network, such as a GSM network, and the terminal device is a mobile station, such as a GSM telephone.

15 14. System as defined in any one of claims 13, characterised in that the terminal device is a GSM telephone, and that the means for using said password management functions are disposed in a subscriber identity module, such as a SIM card.

20 15. System as defined in claim 14, characterised in that, in the connection setup between the subscriber identity module and the server, the transmission of passwords is effected by making use of the called subscriber number.

25 16. System as defined in claim 14 or 15, characterised in that the software means of the subscriber identity module are designed to identify the service on the basis of its identifier data, such as the telephone number, and to append a number
30 of additional digits forming a password to the end of the telephone number of the service during call setup.

35 17. System as defined in any one of claims 13 - 16, characterised in that the subscriber identity module is provided with a service directory containing information specifying the services, the service identifier data and the names of the password files to be used in conjunction with the services.

18. System as defined in claim 17, characterised in that the service directory is provided with a pointer for each service, which pointer has been arranged to point to the first unused password in the set of passwords and, after this password has been used, to move on to point to the next unused password in sequence.

19. System as defined in any one of claims 13 - 18, characterised in that the means for ordering new passwords and transmitting them between the server and the subscriber identity module comprise the short-message service (SMS-PP service) of the GSM network.

(57) ABSTRACT

The invention relates to a procedure and a data communication system in which a service provider gives the user of a service a set of expendable passwords that the user can use to access the service via a telecommunication and/or data network. The system comprises a user's terminal device provided with means for sending a password at log-on to the service, and a server to which the terminal device sets up a connection and which comprises means for identifying the password and for allowing/denying access to the service on the basis of the password supplied. The terminal device comprises means for storing a set of passwords and for selecting the right password from the stored set of passwords at log-on to a predetermined service to allow automatic addition of the password to a connection setup signal to be transmitted from the terminal device to the server.